

Bupi UK Model 3 HP Aqueous Parts Washer

Sorry, this machine is no longer available

We might be able to meet your requirements with other [Spray & Jet Cleaning](#) machines.



Stock No	DR1002
Manufacturer	Bupi UK
Model	3HP
Serial	9335
Work Envelope (WxDxH mm)	820 x 820 x 750mm
Process Stages	Single stage hot wash
Other Info	Industrial heavy duty machine
Weight (kgs)	950kgs
External Dimensions (WxDxH mm)	2000 x 1350 x 2550mm

Description

The Bupi Cleaner is known throughout the industry for its robust design and simple application and maintenance. The Standard chamber washing machine in the fold-down door version stands out due to its technical features, simple design and compact dimensions, built with excellent craftsmanship down to the smallest detail.

The machine is constructed from coated mild steel with stainless-steel parts and components that come in to contact with the cleaning agent.

The load is placed in a basket, which is mounted on a trolley and inserted directly through open door into the wash chamber

During the washing cycle, the basket is slowly rotated using a friction drive, which subjects the load to the hot washing solution, applied to all sides through the multi spray jets.

Technical specification of type 3 HP degreaser:

- Main Dimensions approx. (without additional fittings)
- Width 1956 mm
- Width with open electric switchbox door open 2760 mm
- Depth 1330 mm
- Height (upper edge treatment chamber) 1640 mm
- Total Height with raised door 2540 mm
- Loading height (upper trolley edge) 776 mm
- Working height from upper trolley edge 700 mm
- Square mesh basket with rounded corners, inside approx. 820 mm
- Mesh basket, diagonal length with rounded corners 1012 mm
- Mesh basket 200 mm
- Wash load weight (working load) max. 700 kg
- Total cleaning unit weight 770 kg
- Power Supply, Three-phase voltage 400 V
- Frequency 50 Hz
- Control voltage 230 V
- Total connected load approx. 15 / 27 KW/A
- Electrical systems in accordance with ENEC
- Spray pressure at the nozzle outlet approx. 4,0 bar
- Technical pump data
- Circulation capacity 22m³/h
- Transport height 45,0 mWS
- Pump motor 5,5 kW
- Electric heating 9 kW

Infinitely variable treatment temperature approx. 70 °C

Washing tank warm-up period (on the basis of a new filling) approx. 1,5 - 2 StdJh

Photographs taken prior refurbishment. Our refurbishment service is not available on all machines.