

## Parker Hiross Parker Hiross Starlette Plus SPL050 Refrigerant Air Dryer

**Sorry, this machine is no longer available**

We might be able to meet your requirements with other [Associated Air Compressor Equipment](#) machines.



Stock No	<a href="#">AS0070</a>
Manufacturer	<a href="#">Parker Hiross</a>
Model	SPL050
Year of Manufacture	2008
Serial	3560480001
CFM/Kw	190
Compressor Type	Hermetically sealed
Other Info	Compact large capacity dryer
Weight (kgs)	58kgs
External Dimensions (WxDxH mm)	560 x 500 x 610mm

### Description

The application of high-quality air ensures continuity and reliability of industrial applications, the highest quality standards for finished products and the optimisation of production costs.

The Marketplace for Surface Technology.  
New and Used Process Equipment & Machinery.  
*Machine Datasheet*



Parker Hiross offers a range of refrigerated air drying solutions using advanced refrigeration technology.

Starlette Plus is Parker Hiross' answer to the specific needs of the industrial user.

Starlette Plus safeguards continuous performance and superior efficiency in every industrial compressed air application.

It can easily be adapted to suit all working conditions, maintaining reliable dewpoint control and the lowest possible pressure drops and operating costs.

With its state-of-the-art PlusPack heat exchangers (patent pending) and the most compact dimensions of any system in its class, Starlette Plus is the superior choice for any compressed air treatment application.

Features:

- Reliable air-tight piston compressors which do not require preheating.
- Simple and secure refrigeration circuits which do not require adjustment during operation and undergo vigorous quality testing in production.
- Large adjustable condenser and fan compartments to guarantee optimum performance even in extreme conditions.
- Security protection in the refrigeration circuit, increasing reliability and safeguarding the air dryer.
- Simple disassembly, with easy access to the internal components for efficient maintenance.
- Drain positioned in a niche, allowing easy access without the need to remove the top panel

Technical details of the SPL050

Flow capacity; m<sup>3</sup>h 300 m<sup>3</sup>m 5,

Connections 1 1/2" bsp

absorbed power 0,85kw

Power supply 230v / 1ph / 50Hz / 1.1kw / 6.4A

min/max air pressure - 14.5/232psi

min/max ambient temp - 5°C/50°C

refrigerant - 134a / 0.82kg / 29oz

**Photographs taken prior refurbishment. Our refurbishment service is not available on all machines.**