The Marketplace for Surface Technology. New and Used Process Equipment & Machinery.

Machine Datasheet



Heraeus UT6760 Double Door Oven

Sorry, this machine is no longer available

We might be able to meet your requirements with other <u>Laboratory & Bench Top Ovens</u> machines.



Stock No Manufacturer Model

Internal Size (WxDxH mm)

Max Temp Weight (kgs)

Serial

External Dimensions (WxDxH mm)

OT1387 Heraeus UT 6760 92112538

1000 x 520 x 1290mm

300°C 220kgs

1200 x 800 x 1810mm

Description

Heraeus UT 6760 heating and drying oven

The multi-talented Heraeus 6000 series provides almost unlimited capacity and is particularly adaptable, with controllable fan extraction rate, digital display temperature and and over temperature protection which are





The Marketplace for Surface Technology. New and Used Process Equipment & Machinery.

Machine Datasheet



easily controlled.

Electronically controlled Heraeus 6000 preheating chamber assuring temperature accuracy and reproducible results with a temperature range from 5 °C above ambient temperature to 300 °C

Features

- Safety 2 x Tilt-proof shelves with front ventilation flap slide and rear exhaust duct
- Efficient high thermal insulation ensuring low surface temperatures and economical in operation
- High performance, extremely short heat-up and recovery times with 5.6 kW installed heaters,
- **Wide temperature range** the ovens can reach temperatures between ambient to 300°C with Independent adjustable temperature safety device, with visual temperature alarm
- Construction Powder coated mild steel outer casing and Stainless steel internal chamber

Technical Specification model UT 6760

Dimensions (w x h x d)
Outer casing mm 1200 x 800 x 1810 mm
Height feet/roller mm 106
Inner chamber
Total volume L 689
Internal dimensions (w x h x d)
1000 x 520 x 1290 mm
Shelves stand.. No. 2/2
Weight empty kg 220

Temperature

Temperature range°C 300

Spatial temperature deviation

at 70 °C ± °C 2/2 at 150 °C ± °C 5/4 at 300 °C ± °C 6/7

Temp. deviation

over time ± °C < - 0.5 Electrical data Rated voltage N 400.3~/N (50/60 Hz)3) 8.4 A kW 5.8





The Marketplace for Surface Technology. New and Used Process Equipment & Machinery.

Machine Datasheet



Photographs taken prior refurbishment. Our refurbishment service is not available on all machines.

