

## Seftec Hot Wax Coating Unit

**Sorry, this machine is no longer available**

We might be able to meet your requirements with other [Powder coating, wet paint plant & equipment](#) machines.



Stock No	<a href="#">TT107</a>
Model	Dip seal
Work Envelope (WxDxH mm)	550 x 500 x 200
Other Info	Suitable for a wide range of coatings
External Dimensions (WxDxH mm)	930 x 950 x 3000

### Description

SEFtec dip seal machine for use with non-toxic hot melt removable plastic and wax coatings. Mainly used in either the lost wax process for castings or for finished part protection coverage.

Used in diverse industries Worldwide such as Investment casting, Engineering, Wine Bottling, Pharmaceutical, Dental Tooling, Tooling, Resharpener, Offshore Oil Rigs and other Industrial applications.

**Dip seal plastic protective coatings can be applied in limitless applications including:**

The Marketplace for Surface Technology.  
New and Used Process Equipment & Machinery.  
*Machine Datasheet*



- Protection of machine tools from nicks, cuts, corrosion and moisture.
- Protective coatings for masking parts to be plated
- Wax mould or tree production for the lost wax casting process
- Marine applications
- Glass breakage
- Can be used and reused as protective packaging that optimizes your cost effectiveness.
- Protection of items during shipping and handling
- Protection of items during long storage periods
- Sealing of bottles and other containers
- Protect sharp edges from burrs or accidental cuts
- Protection of parts from salt spray and/or corrosion

SEFtec's quality tanks are fabricated from stainless steel, and enclosed in a insulated polished stainless steel jacket. Constructed for even heating The dip seal tank features Electronic thermostatic controls for constant preset working temperatures. Rectangular model with an internal capacity 550 x 500 x 200 mm deep.

The dipping tank is complimented by a pneumatic lifting swing arm for ease of loading and maximum operator safety with an removable basket with dimensions of 400 x 240 x 130 mm deep.

Typically used within the operating range of 60-300°C temperature span for all of the most commonly available dip seal coatings.

**Photographs taken prior refurbishment. Our refurbishment service is not available on all machines.**