

# Riley Surface World NEW PRODUCTS

CLEANING &  
DEGREASING

## Riley Ultra-World Ultrasonic and Conventional Cleaning Systems Hot Air Condensing Dryer Units

The Ultra-World Hot Air Condensing Dryer range can be combined with our bench top or industrial cleaning tanks to provide rapid and efficient component drying during or at the end of the cleaning process. They can also be introduced as part of a multi-stage integrated cleaning system or included in a complete process plating or finishing production line.

There are 6 models with internal tank dimensions up to 700 x 600 x 500 mm deep. They include fan-assisted heating up to 80°C, power capacity up to 9500 watts and optional digital controls.

### TECHNICAL SPECIFICATIONS

MODELS		T58	T78	T98	T120	T160	T200
Tank Material		Fabricated Stainless Steel					
Internal Dimensions (mm)	Length	600			700		
	Width	500			600		
	Depth	250	300	400	300	400	500
Outlet		BSP					
Case Material		Rigid Stainless Steel					
Overall Dimensions (mm)	Length	700			800		
	Width	600			700		
	Depth	450	500	600	500	600	700
Baskets		Standard Baskets utilised					
Lid Material		Brushed Stainless steel					
Timer Control (mins)		0 to 30 + Continuous					
Heating Control		0° to 80°C					
Fan Double Impeller		Airflow 1280m3/Hr					
Motor Suppression		Yes					
Mains Voltage (v)		380/440v 50/60Hz 3PH+N+E					
Power Consumption (watt)		6500			9500		
Noise Level (dBA)		Approx 82					
Weight Approx (kg)		70	80	90	105	125	140
Options		Digital Control					
		Floor Standing 850HT to rim.					

Specifications may change without notice



European Association of  
Machine Tool Merchants



Machinery Dealers  
National Association  
of USA

Riley Industries Ltd.

Redhouse Industrial Estate, Middlemore Lane West, Aldridge, West Midlands, WS9 8BG, UK

T: +44 (0) 1922 45 8000 F: +44 (0) 1922 45 8001

E: [info@rileysurfaceworld.co.uk](mailto:info@rileysurfaceworld.co.uk) [www.rileysurfaceworld.co.uk](http://www.rileysurfaceworld.co.uk)