

Home > Surface Treatment Process Plant & Equipment > Process Tanks >

Harlequin Storage Tank



Stock Code: TR037

Model: 2500BFS/A BioFuel Station

New or Used: Used (Second Hand)

Other Info: Storage and dispensing of Diesel oil

Weight: 200 kg

External Dimensions (WxDxH): Ø2090 x 1930 mm

2500BFS/A BioFuel Station

Bunded plastic BioDiesel storage and dispensing tank, rotationally moulded from a premium, specialist grade of BioDiesel resistant Medium Density Polyethylene and supplied complete with:

Home > Surface Treatment Process Plant & Equipment > Process Tanks >

Harlequin Storage Tank

- * 2" Fill Point with Screw Cap
- * 4" Inspection Point with Screw Cap
- * Vent
- * Apollo Electronic Oil Tank Contents Gauge
- * Bund Warning Alarm
- * LRC Failsafe Overfill Prevention Capability
- * Lockable Access
- * 240v Electric Pump
- * 10 micron Fuel Filtration System
- * 4 metre Fuel Delivery Hose with Automatic Shut Off Nozzle
- * Mechanical Flow Meter with Resettable Batch Totaliser
- * Emergency Isolation Switch
- * Bulkhead Light

Applications

Suitable for the storage and dispensing of Diesel and BioDiesel grades up to B100, produced in accordance with the requirements of BS/IS EN14214 – including national Summer and Winter Fuel requirements for CFPP(1) in the UK and Republic of Ireland - at agricultural, commercial, industrial and institutional premises.

Satisfies or exceeds all applicable product requirements detailed within:

- * The Control of Pollution (Oil Storage) (England) Regulations 2001
- * The Control of Pollution (Silage, Slurry and Agricultural Fuel Oil) Regulations 1991
- * The Control of Pollution (Silage, Slurry and Agricultural Fuel Oil) Regulations (Northern Ireland) 2003
- * The Water Environment (Oil Storage) (Scotland) Regulations 2006
- * Environmental Alliance Pollution Prevention Guidelines PPG 2

(1) CFPP is the Cold Filter Plug Point which indicates the temperature at or below which a fuel may begin to cause operational problems. British Standard BS EN14214 and Irish Standard IS EN14214 states Summer and Winter requirements within the UK and Republic of Ireland as -5 degrees Celsius and -15 degrees Celsius respectively.

Details:

Diameter: 2090 mm

Height: 1930 mm

Weight: 200 kg

Actual Capacity: 2716 litres

Nominal Capacity: 2580 litres

List price new £4492.50



Home > Surface Treatment Process Plant & EquipmentProcess Tanks >

Harlequin Storage Tank

View Harlequin Storage Tank on our web site at <http://www.rileysurfaceworld.co.uk/machines/24337.htm>

PHOTOGRAPHS TAKEN PRIOR TO REFURBISHMENT.

