

Home > Cleaning & Degreasing Machinery > Spray & Jet Cleaning >

## Wheelabrator Cleantek 600 Ø Basket Spray Wash



**Stock Code:** DY1314

**Manufacturer:** Wheelabrator

**Model:** L55CM

**Year of Manufacture:** 2016

**Serial:** 0755CM899LDV

**New or Used:** Used (Second Hand)

**Work Envelope (WxDxH mm):** 580 Dia. x 90

**Process Stages:** 1

**Other Info:** Includes Oil Skimmer // Single Phase

**Weight:** 125

**External Dimensions (WxDxH):** 1050 x 890 x 1020

Wheelabrator Cleantek L55CM Top Loading - Aqueous Washing Machine

The L55CM is a fully stainless steel constructed cellular type rotary hot wash spray machine, which uses town's water and any number of environmentally friendly detergents.

Constructed with extremely strong build rigidity and quality in mind. Designed to automatically wash / degrease a wide variety of industrial and commercial components.



Home > Cleaning & Degreasing Machinery Spray & Jet Cleaning >

## Wheelabrator Cleantek 600 Ø Basket Spray Wash

The operation is very simple, you just load the basket, close the lid, press start. The cycle is adjustable for both time and temperature and resets automatically each time the lid is opened at the end of the cycle.

The wash basket remains stationary while the spray boom revolves around it. This means that any delicate components will not get damaged by shock movements.

The inbuilt stainless steel pumps deliver over 150 litres of water every minute providing plenty of power to remove stubborn and difficult contamination from the components. This water is returned to the tank and is filtered to remove debris via an easily accessible collection filter basket.

The spray bars fully envelope the basket offering a full 360°C wash pattern. For ease of loading larger parts, the spray bars can be split in the middle and pushed aside to allow the parts to be loaded directly from overhead with a crane or forklift unit.

The wash cycle of the most components are typically cleaned and flash dried within just a few minutes.

Specification:

Basket diameter: 600mm Useable height: 390mm Temperature Range: 20 - 75 degrees Celsius Required Power:  
Single phase 240 vac // 18 amps // 3.55 kW

STANDARD FEATURES: Fully stainless steel internal and external panels Insulated double skin construction Fully automatic

ADDITIONAL FITTED FEATURES:

Internally mounted oil skimmer.

View Wheelabrator Cleantek 600 Ø Basket Spray Wash on our web site at  
<https://www.rileysurfaceworld.co.uk/machines/29355.htm>

PHOTOGRAPHS TAKEN PRIOR TO REFURBISHMENT.