Vixen Surface Treatments Top Loading Single Stage Basket Spray Wash

Sorry, this machine is no longer available

We might be able to meet your requirements with other Spray & Jet Cleaning machines.

Stock No	DY1323
Manufacturer	Vixen Surface Treatments
Model	JW99
Condition	Good Condition, Current Model, Seen powered at RSW
Work Envelope (WxDxH mm)	Basket 960 Ø x 280 (Max depth 425mm.)
Process Stages	Single stage wash
Other Info	All wet surfaces are stainless steel.
Weight (kgs)	350
External Dimensions (WxDxH mm)	1750 x 1700 x 1140mm*

Description

Jetwash JW99 Top Loading - Aqueous Washing Machine

The Jetwash JW99 is a stainless steel constructed cellular type rotary hot was spray machine , which uses towns water

and any number of environmentally friendly detergents.

The unit consists of a steel clad double skin construction over a stainless steel machine, with an 18 mm injected cavity insulation gap offering maximum thermal insulation to the hot water tank and an extremely strong build rigidity.

Designed to automatically wash / degrease a wide variety of industrial and commercial components.

The operation is very simple, you just load the basket , close the lid , press start. The cycle is is adjustable for both time and temperature resets automatically each time the lid id opened at the end of the cycle.

The wash basket remains stationary while the spray boom revolves around it . This means that any delicate components will not get damaged by shock movements.

The inbuilt stainless steel pumps deliver over 150 litres of water every minute providing plenty of power to remove stubborn and difficult contamination from the components. This water is returned to the tank and is filtered to remove debris via an easily accessible collection filter basket.

The spray bars fully envelope the basket offering a full 360° wash pattern. For ease of loading larger parts, the spray bars can be split in the middle and pushed aside to allow the parts to be loaded directly from overhead with a crane or forklift unit.

The wash cycle of the most components are typically cleaned and flash dried within just a few minutes.

STANDARD FEATURES

*Fully stainless steel internal panels

*Insulated double skin construction

*Fully automatic

ADDITIONAL FITTED FEATURES

*Internal construction is fully stainless steel with steel clad insulation and externally mounted oil collection trap.

Photographs taken prior refurbishment. Our refurbishment service is not available on all machines.