

Dry Filter Bench Spray Booth



Stock Code: GA846

Model: Bench Level Spray Booth

New or Used: Used (Second Hand)

Approx Duty CFM / M³/Hr : Able to Contain Overspray

Filter Area ft² / m²: 1.35m²

Other Info: Galvanized Steel Construction

Weight: 240

External Dimensions (WxDxH): 1670 x 1300 x 2850

Dry Filter Bench Level Spray Booth

Internal working area size - 1500mm wide x 1100mm high x an average of 750mm deep (tapered back).

Bench level spray booth operates under the same principle as full size booth but with a work surface at a convenient height to allow the painting of small components.

Bench type spray booth is 2590mm high, 1300mm deep and has an integrated extraction fan set up for connection to a suitable extraction system. Including outlet connection of Ø300mm & belt driven fan via a 1400 rev/min motor.

The Theory

Because most wet paint overspray is sticky, it can be arrested by carrying it on an air stream and then trapping the paint particle within either a pleated paper filter, nylon mesh or expanded paper filter.

The air can then pass through the filter and the fumes can be exhausted to atmosphere.



Home > Dust & Fume Extraction Equipment Associated Dust Control Equipment >

Dry Filter Bench Spray Booth

Key features and benefits Option of to use as a fettling bench. Simple, low cost maintenance. Complies with current health and safety legislation. Low-cost means of providing a safe environment. Increased quality of finished work. Makes working conditions healthier and more pleasant for operatives. Eliminates extra cleaning, previously caused by overspray. Specifications: Galvanized steel construction. Filter sizes - 1500mm x 900mm x 70mm thick. Roof mounted twin fluorescent light to allow light into the work area. Shelf height is 900mm from the floor. Fan stop/start switch box.

View Dry Filter Bench Spray Booth on our web site at <https://www.rileysurfaceworld.co.uk/machines/30741.htm>

PHOTOGRAPHS TAKEN PRIOR TO REFURBISHMENT.

